

1. Unique identification product code:

MASTERS 80

2. Batch number, batch or any other identifying product item:

Art. 11, paragr. 4

Batch number displayed on the packaging

3. Uses of the construction product provided by the manufacturer in accordance with the harmonised technical specifications.:

EN 15651-1 : F-EXT-INT (sealant for facade for interior and exterior application)

EN 15651-2 : G (sealant used for sealing glazing applications)

EN 15651-3 : S (sealant for joints in sanitary areas)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 paragr. 5

MASTICI VOTTERO S.N.C.
Via Torino 44,
10040 La Cassa (TO) ITALIA

5. Name and address of the authorized representative whose mandate covers the tasks specified in Article 12

Paragr. 2 :

N.R.

6. Systems of evaluation and verification of the construction product performances according to annex V:

The notified body SKZ Tecona GmbH (NB01213)
performed the determination of the product-type
on the basis of type testing under system 3, issued
report:

EN 15651-1: F-EXT-INT CLASS – 12,5 E

Pre-Conditioning Method A (according to ISO 8340)
 Substrate Glass without primer
 Aluminium without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501) | Class E | EN 15651-1 : 2012 |
| Release of chemicals dangerous to the environment and health | See product safety data sheet | |
| Water tightness and air tightness | | |
| Resistance to flow (ISO 7390) | ≤ 2 mm | |
| Loss of volume (ISO 10563) | ≤ 30 % | |
| Tensile properties at maintained extension after immersion in water (ISO 10590) | No failure (60%) | |
| Tensile properties at maintained extension at (ISO 8340) | No failure (60%) | |
| Durability (EN 15651) | Pass | |

EN 15651- 2: G

Pre-Conditioning Method A (according to ISO 8340)
 Substrate Glass without primer
 Aluminium without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501) | Class E | EN 15651-2 : 2012 |
| Release of chemicals dangerous to the environment and health | See product safety data sheet | |
| Water tightness and air tightness | | |
| Loss of volume (ISO 10563) | ≤ 20 % | |
| Resistance to flow (ISO 7390) | ≤ 2 mm | |
| Adhesion and cohesion properties after exposure to artificial light (ISO 11431) | No failure | |
| Elastic recovery (ISO 7389) | ≥ 70 % | |
| Durability | Pass | |


EN 15651-3: S CLASS – XS1

Pre-Conditioning Method A (according to ISO 8340)
 Substrate Glass without primer
 Aluminium without primer

| Essential characteristics | Performance | Harmonised technical specification |
|---|-------------------------------|------------------------------------|
| Reaction to fire (EN 13501) | Class E | |
| Release of chemicals dangerous to the environment and health | See product safety data sheet | |
| Water tightness and air tightness | | |
| Resistance to flow (ISO 7390) | ≤ 2 mm | |
| Loss of volume (ISO 10563) | ≤ 20 % | |
| Tensile properties at maintained extension after immersion in water (ISO 10590) | No failure | |
| Evaluation of the action of microorganisms (ISO 846) | 1 | |
| Durability | Pass | |

EN 15651-3 : 2012

The responsibility of this performance statement is exclusively of the producer referred to point 4.



Vottero Stefano

Stefano
 MASTICI VOTTERO s.n.c.
 Via Torino, 44
 10040 LA CASSA (TO)

Liability restrictions

The content of this statement of performance is provided in good faith on our experience bases and knowledge. The user is responsible for verifying the product suitability for the intended use regardless of the above applications. Mastici Vottero does not give any guarantee regarding specific applications; in addition, the user must check the safety data sheet to take note of the guidelines for product use.

For technical information, product quality/safety please contact:
 MASTICI VOTTERO s.n.c.
 10040 La Cassa (TO) - via Torino 44
 info@masticivottero.com
 www.masticivottero.com