



Product description

Bituminous adhesive with pasty consistency for bonding rubber and semi-rigid PVC on concrete, wood, bituminous conglomerates and metals.

Specifications

- ready-to-use
- easy-to-apply
- applicable both horizontally and vertically
- drying time depending on the thickness of the layer applied and on the kind of support

Application areas

- BITUMPHALTE 130 can be used for rubber and vinyl floorings bonding and fastening signage cones on the road surface

Use of the product

Target surfaces must be completely dry, clean and free of greasy oils and dust. BITUMPHALTE 130 is ready to use and it can be settled with a spatula. The drying times vary depending on the type of substrate, the thickness of the layer and the ambient temperature. Due to high thixotropy, the product is easy to apply both horizontally and vertically. Dirty gear, clothes, and dirty hands can be cleaned with common synthetic thinner or nitro.

Package

tin bucket 5 kg
drums 20 kg

Colours



black
nero
RAL 9005

Safety notes

Safety data sheet available on request

BITUMPHALTE 130 - Product data

General characteristics	Inspection method	unit	Value
Appearance			Tixotropic paste
Colour			Black
Stability in original packages		[months]	24
Dry residue at 130°C	EN ISO 3251	[%]	73 / 81
Viscosity Brookfield at 25°C (gir. N. 7 - 10 rpm)	EN ISO 3219		850 P ± 150
Specific weight at 20°C	EN ISO 2811-1	[kg/l]	1,10 ± 0,03
Closed cup flash point		[°C]	> 30
Operating temperature		[°C]	-10 / +35

These figures are only intended as a guide and should not be used in preparing specifications.



The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

The management system has been certified according to DIN EN ISO 9001 and DIN EN ISO 14001

For technical, quality, or product safety questions, please contact:
 MASTICI VOTTERO s.n.c.
 10040 La Cassa (TO) - via Torino 44
 info@masticivottero.com
 www.masticivottero.com