

1. Unique identification product code:

**MASTERS POLYMER F-35**

2. Batch number, batch or any other identifying product item:

Art. 11, paragr. 4

**Batch number displayed on the packaging**

3. Uses of the construction product provided by the manufacturer in accordance with the harmonised technical specifications.:

**EN 15651-1 : F-EXT-INT-CC (sealant for facade for interior and exterior application (intended for use in cold climates))**

**EN 15651-3 : G (sealant for joints in sanitary areas)**

**EN 15651-4 : PW-INT (sealant for moment joints in floors for interior application)**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 paragr. 5

**MASTICI VOTTERO S.N.C.**  
**Via Torino 44,**  
**10040 La Cassa (TO) ITALIA**

5. Name and address of the authorized representative whose mandate covers the tasks specified in Article 12

Paragr. 2 :

**N.R.**

6. Systems of evaluation and verification of the construction product performances according to annex V:

**The notified body TECNALIA RESEARCH & INNOVATION (NB1292) performed the determination of the product-type on the basis of type testing under system 3, issued report:**

**EN 15651-1: F-EXT-INT-CC Class – 25 HM**

Pre-Conditioning Method A (according to ISO 8340)  
 Substrate Glass without Primer

Essential characteristics	Performance	Harmonised technical
Reaction to fire (EN 13501)	Class E	
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	0 mm	
Loss of volume (ISO 10563)	≤ 3 %	
Tensile properties at variable temperature (ISO 9047)	No failure	
extension after immersion in water (ISO 10590)	No failure	
Modulus in elongation at -20°C (ISO 8339)	0,89 MPa	EN 15651-1 : 2012
Modulus in elongation at +23°C (ISO 8339)	0,83 MPa	
Tensile elongation (ISO 8339)	No failure	
Tensile properties at maintained extension at -30°C (ISO 8340)	No failure	
Tensile properties at maintained extension at +23°C (ISO 8340)	No failure	
Durability (EN 15651)	Pass	

**EN 15651-3: G Class – XS1**

Pre-Conditioning Method A (according to ISO 8340)  
 Substrate Glass without primer

Essential characteristics	Performance	Harmonised technical
Reaction to fire (EN 13501)	Class E	
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Resistance to flow (ISO 7390)	0 mm	
Loss of volume (ISO 10563)	≤ 3 %	
Tensile properties at maintained extension after immersion in water (ISO 10590)	No failure	EN 15651-3 : 2012
Tensile properties at maintained extension at +23°C (ISO 8340)	No failure	
Tensile properties at variable temperature (ISO 9047)	No failure	
Evaluation of the action of microorganisms (ISO 846)	1	

**EN 15651-4: PW-INT CLASS - 25HM**

Pre-Conditioning Method A (according to ISO 8340)  
 Substrate Mortar without Primer

Essential characteristics	Performance	Harmonised technical
Reaction to fire (EN 13501)	Class E	
Release of chemicals dangerous to the environment and health	See product safety data sheet	
Water tightness and air tightness		
Loss of volume (ISO 10563)	≤ 3 %	
Adhesion and cohesion properties at maintained extension after immersion in water (10590)	Superato	
Modulus in elongation at +23°C (ISO 8339)	0,83 MPa	EN 15651-4 : 2012
Modulus in elongation at -20°C (ISO 8339)	0,89 MPa	
Tensile properties at maintained extension at -30°C (ISO 8340)	No failure	
Tensile properties at maintained extension at +23°C (ISO 8340)	No failure	
Durability	Pass	

The responsibility of this performance statement is exclusively of the producer referred to point 4.

Vottero Stefano

*Stefano*  
 MASTICI VOTTERO s.n.c.  
 Via Torino, 44  
 10040 LA CASSA (TO)

**Liability restrictions**

The content of this statement of performance is provided in good faith on our experience bases and knowledge. The user is responsible for verifying the product suitability for the intended use regardless of the above applications. Mastici Vottero does not give any guarantee regarding specific applications; in addition, the user must check the safety data sheet to take note of the guidelines for product use.

For technical information, product quality/safety please contact:  
 MASTICI VOTTERO s.n.c.  
 10040 La Cassa (TO) - via Torino 44  
 info@masticivottero.com  
 www.masticivottero.com